

DATA SHEET

Code: VMT-271IP

MONITOR TCP/IP, VGA, 2xVIDEO, S-VIDEO, HDMI, AUDIO VMT-271IP 27 " VILUX

CCTV professional monitor with IP cameras support function and solid metal housing with additional layer for matrix protection.

To the monitor can be connected via a switch 4 cameras operating at a resolution of 1280×720 or 2 cameras with a resolution of 1920×1080 .

The LED matrix illumination technology allows to real colors reproduction, 40% lower current consumption and much lower failure rate compared to normal LCD monitors with CCFL illumination. Interesting solution is placing the speakers of the back side of housing. It does not bother listening to the AUDIO from the recorder at the same time does not reduce the area of the monitor front panel.

The device is designed to continuous work in closed spaces.



Screen size:	27 "
Native resolution:	1920 x 1080 px
Aspect ratios:	16:9
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	 TCP/IP - The list of compatible devices is available below, PAL/NTSC
Contrast:	1000 : 1
Brightness:	450 cd/m ²
Viewable angles:	170 ° horizontal 170 ° vertical
Response time:	5 ms
Speakers built-in:	2 x 2.5 W



VMT-271IP



DATA SHEET

Signal connectors:	 Port LAN - RJ-45 socket Composite Video (BNC) sockets: 2x in, 1x out 1x VGA 1x HDMI 1x S-VIDEO Audio: 1x Jack (for VGA) 2x Cinch L/R (for Video 1/2) 2x Port USB - Mouse support
Housing type:	Metal
Monitor mounting standard:	VESA 100
Power supply:	230 V AC
Power consumption:	 < 50 W (operation) < 1 W (Standby mode)
Monitor control:	OSD - by IR remote controller or monitor control keys
Main features:	 3D Comb Filter 3D Noise Reduction PIP and POP functions - picture in picture and two pictures side by side Auto Picture Adjustment
Operation temp:	-10 °C 50 °C
Weight:	9.75 kg
Dimensions:	652 x 400 x 62 mm
Supported languages:	English, Chinese, French, Spanish, German, Polish, Portuguese, Russian, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years

