

Code: LUMENA-1M1-12

IP PTZ CAMERA INDOOR **LUMENA-1M1-12** - 1.3 Mpx 2.8 mm

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition. Included camera software enables management and integrated monitoring of many network cameras.



| | |
|----------------------------------|---|
| Standard: | TCP/IP |
| Sensor: | 1/3 " OmniVision OV1035 CMOS |
| Digital Image Processor: | Hisilicon 3518C |
| Matrix size: | 1.3 Mpx |
| Resolution: | 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p 640 x 480 |
| Scanning system: | Progressive |
| Lens: | 2.8 mm |
| View angle: | <ul style="list-style-type: none"> • 81 ° (manufacturer data) • 76 ° (our tests result) |
| Optical zoom: | — |
| Range of IR illumination: | 15 m |
| S/N ratio: | ≥ 50 dB |
| Video output: | — |
| Rotation speed (manual control): | 0.1 °/s ... 12 °/s (horizontal) 0.1 °/s ... 10 °/s (vertical) |
| Preset rotation speed: | 15 °/s |

| | |
|----------------------------|---|
| Horizontal rotation range: | 355 ° |
| Vertical rotation range: | 0 ° ... 93 ° |
| RS-485 interface: | — |
| Number of presets: | 220 |
| Horizontal scan: | ✓ |
| Route settings: | 3 |
| Image compression method: | H.264 |
| Protections: | Overvoltage |
| Alarm inputs / outputs: | — |
| Network interface: | 10/100 Base-T (RJ-45) |
| Network protocols: | TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP |
| Bitrate: | 256 ... 10000 kbps |
| ONVIF: | ✓ |
| Mobile phones support: | Connection in cloud technology only • Android: Free application Cloudlens • iOS (iPhone): Free application Cloudlens |
| Main features: | <ul style="list-style-type: none"> • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode (color/b&w/auto) |
| Power supply: | 12 V DC / 0.83 A (power adapter not included) |
| Housing: | Dome, Plastic |
| Color: | Ivory |
| Operation temp: | -15 °C ... 60 °C |
| "Index of Protection": | IP40 |
| Weight: | 0.420 kg |
| Dimensions: | Ø 137 x 112 mm |
| Guarantee: | 2 years |