

Code: PRO-PLUS

PIR DETECTOR **PRO-PLUS** PARADOX

The PRO-PLUS passive PIR detector designed to use indoors. The advanced signal analysis algorithms ensure stable operation and low level of false alarms.



| | |
|----------------------------------|-------------------------|
| Application: | Indoor |
| Pyroelectric sensor: | Double |
| Sensor type: | Passive Infra Red (PIR) |
| Range: | 11 x 11 m |
| Detection angle: | 88.5 ° |
| Recommended installation height: | 2.1 ... 2.7 m |
| Sensitivity adjustment: | — |
| Autodiagnostics: | — |
| Pet immunity: | — |
| Prealarm feature: | — |
| Maximal outputs load: | 28 V DC / 150 mA |
| Alarm outputs: | NC |
| Alarm time: | 3 s |
| Target speed range: | 0.2 ... 3.5 m/s |

| | |
|-----------------------------------|---|
| Digital temperature compensation: | ✓ |
| Power supply: | 9 ... 16 V DC |
| Maximal current consumption: | 31 mA |
| Main features: | <ul style="list-style-type: none">• Interchangeable Fresnel lenses• Tamper protections• Auto Pulse Signal Processing• Metal shield protecting from EMI, RFI signals• Test mode• EN 50130-4, EN 55022 |
| Operation temp: | -20 °C ... 50 °C |
| Color: | White |
| Weight: | 0.082 kg |
| Dimensions: | 67 x 93 x 52 mm |
| Country of origin: | Canada |
| Manufacturer / Brand: | PARADOX |
| Guarantee: | 2 years |