

Warning!

Please read the user manual included in this work as it contains important information related with safety of installation and use of the device.

Only persons who read the user manual may use the device.

The user manual must be kept because it may be required in the future. The device is to be used exclusively for purposes specified in this user manual.

The device must be unpacked prior to starting-up. After removing the packaging make sure the device is in working order. If the product has defects, it should not be used until it is repaired.

The product is intended for use at home and commercial use and may not be used for other than intended use.

The manufacturer is not liable for damages resulting from not adhering to the rules contained in the user manual, therefore, we recommend to follow the aforementioned safety rules for operation and maintenance of the device. In this way you will ensure yourself safety and avoid causing damage to the device.

The manufacturer and the supplier are not liable for losses or damages arising out of the product, including financial or intangible losses, loss of profits, income, data, pleasure from use of the product or other products related with it - indirect, incidental or consequential loss or damage. The above provisions apply whether the loss or damage concerns:

1. Deterioration of quality or the lack of operation of the products or products related with it due to damage as well as the lack of access to the product when it is undergoing repair, which results in stoppage the loss of user's time or a break in business activity; 2. Improper results of operation of the product or products related with it;

3. It applies to losses and damages according to any legal category, including negligence and other losses, termination of a contract, expressed or implied guarantee and strict liability (even if the manufacturer or the supplier was notified about the possibility of occurrence of such damages).

Safety measures:

BNC plug crimped on coaxial cable.

cable inserted into the inlet is centered and stopped.

long time.

Particular attention at designing was directed to quality standards of the device where ensuring safety of operation is the most important factor.

The device must be secured against contact with caustic, staining and viscous fluids.





DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

BNC-W/4781-MTC*P10



User Manual Code: BNC-W/4781-MTC*P10 COMPRESSION PLUG BNC-W/4781-MTC*P10 RG6 Triset113 METACON

In package:	10 pcs The price for package
Connector type:	BNC Plug
Attachment of connector elements:	Compression mounting
Application:	Coaxial cable
Dielectric diameter:	max. 4.7 mm
Wire mounting:	Pressing
Cable diameter:	max. 8.1 mm
Shield fastening:	Compression mounting
Watertightness:	¥
Example of application:	• RG6 • HFEK • Triset113
Main features:	 Properly compressed connection is highly resistant to break Watertightness of connector with cable connection Very easy and quick assembly Corrosion resistance Very low loss in the whole operating band To crimp use the crimping tool HT-5082R
Weight:	0.013 kg
Dimensions:	Ø 15 x 42 mm
Manufacturer / Brand:	METACON
Guarantee:	2 years

Connector view from cable assembly side:





User Manual Code: BNC-W/4781-MTC*P10 COMPRESSION PLUG BNC-W/4781-MTC*P10 RG6 Triset113 METACON





Terminating of BNC compression connectors using a compression tool: :



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



User Manual Code: BNC-W/4781-MTC*P10 COMPRESSION PLUG BNC-W/4781-MTC*P10 RG6 Triset113 METACON

PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg

