

Code: DS-7204HQHI-F1/N/A

AHD, HD-TVI, PAL, TCP/IP DVR **DS-7204HQHI-F1/N/A** 4 CHANNELS Hikvision

The DS-7204HQHI-F1/N/A digital recorder with AHD (Analog High Definition) / HD-TVI (High Definition Transport Video Interface), IP - Hikvision and PAL interface is a professional device applicable in surveillance systems. The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-TVI, TCP/IP - Hikvision only, PAL
Video inputs:	4 pcs BNC - HD-TVI / AHD / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs BNC
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	Adjustable bitrate : 32 ... 6144 kbps
Image records resolutions:	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H 704 x 576 - 4CIF 640 x 480 - VGA
Maximal total frame rate:	48 fps @ 1920 x 1080 px, 100 fps @ 1280 x 720 px, 100 fps @ 960 x 576 px 100 fps @ 704 x 576 px 100 fps @ 640 x 480 px
Recording speed adjustment:	1 ... 12 fps @ 1920 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 1 ... 25 fps @ 704 x 576 1 ... 25 fps @ 640 x 480 px for each channel
Operation modes:	• 4 x HD-TVI / AHD / PAL + 1 x TCP/IP - Hikvision only • 2 x HD-TVI + 2 x AHD + 1 x TCP/IP - Hikvision only The recorder allows to combining the AHD / TVI cameras only in pairs
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA



DATA SHEET

External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface:	1 x RJ-45 - 10/100/1000 Base-T
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, DHCP, DDNS, PPPoE, E-mail, NTP, SNMP, UPnP
Mobile phones support:	Android, iOS (iPhone) Android: Free application iVMS-4500 iOS (iPhone): Free application iVMS-4500
Default admin user / password:	admin / 12345
Default IP address:	DHCP or 192.168.1.64
Web browser access ports:	80
PC client access ports:	554 RTSP, 8000
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs:	4 / 1
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	✓
Power supply:	12 V DC / 1.5 A (power adapter included)
Color:	Dark graphite
Weight:	1.165 kg
Dimensions:	315 x 245 x 47 mm
Supported languages:	English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
Guarantee:	3 years