

Code: GT-N78-3636

NVR **GT-N78-3636** 36 CHANNELS +eSATA GEMINI TECHNOLOGY



Standard:	TCP/IP
Supported resolutions:	36 @ 4096 x 2160 px, 36 @ 2592 x 1944 px, 36 @ 2048 x 1536 px, 36 @ 1920 x 1080 px, 36 @ 1280 x 960 px
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio support:	36 Channels
Audio inputs:	Audio from cameras
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.264
Maximal total frame rate:	900 fps @ 4096 x 2160 px, 900 fps @ 2592 x 1920 px 900 fps @ 2048 x 1536 px, 900 fps @ 1920 x 1080 px, 900 fps @ 1280 x 960 px,
Supported hard drives:	8 x 6 TB SATA + 1 x eSATA - The ability to limit a disk space - quota
Recording modes:	Manual, Sensor, Motion detection, Schedule
Image analysis:	Virtual Guard, abandoned/missing object, intrusion
Network protocols:	ONVIF, I8, I8H, I9, RTSP
External storage devices backup:	Records backup at .i8 / .avi format to USB (pendrive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 288 Mbps



DATA SHEET

Network functions:	Network client and browser software IE, Firefox, Opera, Chrome: live view, playback and backup of the records and configuration of the recorder parameters
Operation temp:	-10 °C ... 55 °C
ONVIF:	✓
Mobile phones support:	Port no.: 5800 or access by a cloud (P2P) • Android: Free application Fseye • iOS: Free application Fseye
Default IP address:	192.168.1.189
Default admin user / password:	admin / 888888
Web browser access ports:	80, 554 - Internet Explorer 80, 1935 - Chrome, Firefox, Opera
PC client access ports:	5050, 5051, 5052
Mobile client access ports:	5800
RTSP URL:	rtsp://ip_address:554/ch01.264 - Main stream, first channel rtsp://ip_address:554/ch01_sub.264 - Sub stream, first channel
Alarm inputs / outputs:	4 / 4
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	230 V AC
Weight:	7.7 kg
Dimensions:	480 x 480 x 98 mm 2 U Rack 19"
Supported languages:	English, Polish
Country of origin:	China
Manufacturer / Brand:	GEMINI TECHNOLOGY
Guarantee:	2 years