

Code: PFM710

## EXTENDER VGA **PFM710** DAHUA

The PFM710 extender enables the VGA signal transmission for distance up to 75 m via UTP cable. The transmitter converts the VGA signal, what enables its transmission via twisted-pair cable.

The transmitter and receiver are sold as a set and a both devices need to be used for complete channel transmission.

**Transmitter and receiver are in the kit.**



Device type:	Passive
Video transmission range:	75 m @ 640 x 480
Symmetrical socket impedance:	100 Ω
Connectors type:	<ul style="list-style-type: none"> <li>• 1 x VGA - Socket</li> <li>• 1 x RJ-45 - Socket</li> </ul>
Power supply:	—
Resolution:	<ul style="list-style-type: none"> <li>• 1920 x 1200 px WUXGA @ 20 m (our tests result),</li> <li>• 1280 x 1024 px SXGA @ 40 m (our tests result),</li> <li>• 1280 x 768 px WXGA,</li> <li>• 1024 x 768 px XGA,</li> <li>• 800 x 600 px SVGA,</li> <li>• 640 x 480 px VGA @ 75 m (manufacturer data)</li> </ul>
Bandwidth:	≤ 120 MHz
Grounding:	via grounding bolt
Operation temp:	0 °C ... 55 °C
Permissible relative humidity:	≤ 95 %
Weight:	0.11 kg
Dimensions:	85 x 64 x 28 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>