

Code: BCS-DMIP1400IR-E-III

IP CAMERA **BCS-DMIP1400IR-E-III** - 4.0 Mpx, 2.8 mm

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 2688 x 1520 (4.0 MPx). Included camera software enables management and integrated monitoring of many network cameras.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Camera is according to IP66 Index of Protection norm.



Standard:	TCP/IP
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	4.0 Mpx
Scanning system:	Progressive
Resolution:	2688 x 1520 - 4.0 Mpx , 2560 x 1440 - 3.6 Mpx , 2304 x 1296 - 3.0 Mpx , 1920 x 1080 - 1080p , 1280 x 1024 - 1.4 Mpx , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	106 °
Range of IR illumination:	30 m
S/N ratio:	> 50 dB
RS-485 interface:	—
Memory card slot:	—
Image compression method:	H.264 / MJPEG



DATA SHEET

Alarm inputs / outputs:	—
Audio:	—
Bitrate:	24 kb/s ... 10240 kb/s - H.264
Main stream frame rate:	20 fps @ 4.0 Mpx 25 fps @ 3.0 Mpx
Network interface:	10/100 Base-T (RJ-45)
Network protocols:	HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, QoS, UPnP, NTP, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP
WEB Server:	Built-in
Max. number of on-line users:	20
ONVIF:	2.42
Mobile phones support:	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Main features:	• 3D-DNR - Digital Noise Reduction • WDR - 120 dB - Wide Dynamic Range • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Configurable Privacy Zones • Mirror - Mirror image
Power supply:	• PoE (802.3af), • 12 V DC / 500 mA
Power consumption:	≤ 6 W
Housing:	Dome, Metal
Color:	White
Vandal-proof:	—
"Index of Protection":	IP66
Dimensions:	Ø 94 x 80 mm
Weight:	0.348 kg
Supported languages:	English, Polish
Manufacturer / Brand:	BCS
Guarantee:	2 years