

Code: UT2200E-FR/UPS

## UPS **UT2200E-FR/UPS** 2200 VA CyberPower



The UT2200E-FR/UPS UPS is a professional device used to maintain the operation of the components connected to it. The UPS UT CyberPower series has been equipped with the best-in-class housing of fireproof plastic, which provides outstanding fire resistance and helps to minimize possible losses in the case of fire.

Nominal power:	1320 W
Apparent Power:	2200 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	4 ms
Typical battery charge time:	8 hours
Battery:	2 pcs RBP0090 9 Ah
Estimated battery operation time:	<ul style="list-style-type: none"> <li>• 95 minutes @ 60 W,</li> <li>• 70 minutes @ 90 W,</li> <li>• 34 minutes @ 200 W</li> </ul>
Number of outputs:	4 pcs
Protections:	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload protection</li> <li>• Overcharge protection</li> <li>• Protection: DSL / Tel / FAX / Modem - RJ11 / RJ45</li> </ul>

Operation state indication:	<ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Automatic Voltage Regulator (AVR)</li><li>• Compatible with power generators</li><li>• Battery Management Technology - Increased battery life</li><li>• Fireproof housing</li><li>• Built-in EMI, RFI filter</li><li>• Configurable alarm</li></ul>
Application:	<ul style="list-style-type: none"><li>• Surveillance Systems</li><li>• data storage centers</li><li>• network, servers, workstations</li><li>• Industrial Equipment</li></ul>
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	10.63 kg
Dimensions:	298 x 178 x 148 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years