

Code: DHI-XVR4104C

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **DHI-XVR4104C** 4 CHANNELS DAHUA

The DHI-XVR4104C digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	• AHD / HD-CVI / HD-TVI : 960 x 1080, 1280 x 720 • AHD-L / PAL : 960 x 576, 720 x 576 • IP : max. 1920 x 1080
Maximal total frame rate:	• AHD / HD-CVI / HD-TVI : 100 fps @ 960 x 1080 px, 100 fps @ 1280 x 720 px, • AHD / PAL : 100 fps @ 960 x 576 px, 100 fps @ 720 x 576 px • IP : 125 fps @ 1920 x 1080 px
Recording speed adjustment:	1 ... 25 fps @ 1920 x 1080 px - IP 1 ... 25 fps @ 960 x 1080 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px 1 ... 25 fps @ 720 x 576 px for each channel
Operation modes:	• 4 x AHD / HD-CVI / HD-TVI / PAL @ 1080N • 4 x AHD / HD-CVI / HD-TVI / PAL / TCP/IP @ 1080N + 1 x IP @ 1920 x 1080 Mpx
Recording modes:	Manual, Motion Detection, Schedule



DATA SHEET

Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	White
Weight:	0.494 kg
Dimensions:	212 x 205 x 43 mm
Supported languages:	English, Bulgarian, Czech, Finnish, Greek, Polish, Romanian, Serbian, Slovenian, Hungarian
Country of origin:	China
Manufacturer / Brand:	DAHUA
Guarantee:	3 years