DATA SHEET

Code: GT-N716-128128

NVR **GT-N716-128128** 128 CHANNELS +eSATA GEMINI TECHNOLOGY



Standard:	TCP/IP
Supported resolutions:	128 @ 4096 x 2160 px, 128 @ 2592 x 1944 px, 128 @ 2048 x 1536 px, 128 @ 1920 x 1080 px, 128 @ 1280 x 960 px
Video outputs:	2 pcs HDMI 2 pcs VGA
Audio support:	128 Channels
Audio inputs:	1 pcs CINCH Audio from cameras
Audio outputs:	2 pcs CINCH
Image compression method:	H.265 / H.264 / MJPEG
Maximal total frame rate:	3200 fps @ 4096 x 2160 px, 3200 fps @ 2592 x 1920 px 3200 fps @ 2048 x 1536 px, 3200 fps @ 1920 x 1080 px, 3200 fps @ 1280 x 960 px,
Supported hard drives:	16 x 6 TB SATA + 2 x eSATA • The ability to limit a disk space - quota • Possibility of operation the disks in RAID 0/1/5/6/10 array
Recording modes:	Manual, Sensor, Motion detection, Schedule
Image analysis:	Virtual Guard, abandoned/missing object, intrusion
Network protocols:	TCP/IP, HTTP, DDNS, SMTP, DHCP, PPPoE, UPnP, NTP, P2P
External storage devices backup:	Records backup at .i8 / .avi format to USB (pendrive)

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 640 Mbps
Network functions:	Network client and browser software IE, Firefox, Opera, Chrome: live view, playback and backup of the records and configuration of the recorder parameters
Operation temp:	-10 °C ... 55 °C
ONVIF:	✔
Mobile phones support:	Port no.: 5800 or access by a cloud (P2P) • Android: Free application Fseye • iOS: Free application Fseye
Default IP address:	192.168.1.189
Default admin user / password:	admin / 888888
Web browser access ports:	80, 554 - Internet Explorer 80, 1935 - Chrome, Firefox, Opera
PC client access ports:	5050, 5051, 5052
Mobile client access ports:	5800
RTSP URL:	rtsp://ip_address:554/ch01.264 - Main stream, first channel rtsp://ip_address:554/ch01_sub.264 - Sub stream, first channel
Alarm inputs / outputs:	16 / 8
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	22 x 18 motion zones
Mouse support:	✔
IR remote controller in the set:	–
Power supply:	230 V AC
Weight:	15.5 kg
Dimensions:	483 x 590 x 132 mm, 3 U Rack 19"
Supported languages:	English, Polish
Country of origin:	China
Manufacturer / Brand:	GEMINI TECHNOLOGY
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60