

Code: PCS-260E

## GSM COMMUNICATION MODULE **PCS-260E** PARADOX



Number of supported SIM cards:	2
Alarm inputs:	—
Alarm outputs:	—
Telephone numbers to reporting events:	max. 16
Event codes sending messages type:	SMS
Main features:	<ul style="list-style-type: none"> <li>• 4G/3G/2G GSM network operation,</li> <li>• Reporting via GSM to the monitoring station,</li> <li>• Reporting via to the monitoring station,</li> <li>• SMS notification about an alarm or failure,</li> <li>• Sending the text messages (SMS) with event details,</li> <li>• The ability of remote arm/disarm the system by sending a text message (SMS),</li> <li>• Control panel communication supervision,</li> <li>• Installation to SERIAL connector of alarm control panel,</li> <li>• Possibility to connect the wire antenna,</li> <li>• Encrypted transmission - 128 bit,</li> <li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li> </ul>
Transmitter power:	<ul style="list-style-type: none"> <li>• 2 W @ 850 MHz,</li> <li>• 1 W @ 1800/1900 MHz</li> </ul>
Power supply:	12 V DC



# DATA SHEET

Current consumption:	300 mA (operation) 60 mA (Standby mode)
Operation temp:	-20 °C ... 50 °C
Dimensions:	207 x 74 x 21
Weight:	0.150 kg
Manufacturer / Brand:	PARADOX
Guarantee:	2 years