

Code: PR311SE-BK

ACCESS CONTROLLER **PR311SE-BK** ROGER



Outdoor proximity cards and key-fobs reader with controller built-in. Unique 125 kHz standard.

Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	max. 15 cm
Keyboard built-in:	—
Communication:	<ul style="list-style-type: none"> • RS-485 • RACS (Roger)
Selected features of the standalone mode:	<ul style="list-style-type: none"> • 1000 indexed users • Operation with XM-2 I/O extension module (Full Standalone Mode)
Main features:	<ul style="list-style-type: none"> • The ability to add additional reader (bilateral way door control), • 3 programmable input lines NO/NC, • 2 programmable transistor outputs 1A, • One programmable relay output 1.5A/30V, • Door modes (Normal, Locked, Unlocked and Conditionally Unlocked), • Any topology of communication bus, • "Guest" type additional users support defined individually on each controller, • Integration with an alarm system via in/out line ,
Power supply:	10 ... 15 V DC
Average current consumption:	50 mA
Operation temp:	-25 °C ... 60 °C



DATA SHEET

Permissible relative humidity:	10 ... 95 % (non-condensing)
Weight:	0.18 kg
Dimensions:	152.5 x 46 x 23 mm (Standard housing stand) 152.5 x 46 x 35 mm (Thicker housing stand)
Manufacturer / Brand:	ROGER
Guarantee:	3 years

