

DATA SHEET

Code: MS-35X AHD, HD-CVI, HD-TVI, PAL MONITOR **MS-35X** 4.3 "



Service color monitor is very helpful for CCTV system configuration. Due to small sizes it can be very quickly and easily connected to the camera or DVR for configuration their parameters.

The device is powered from battery or power supply adaptor. So, it is the perfect test tool for CCTV systems, as well as for other devices with AHD / HD-CVI / HD-TVI / PAL output. An additional advantage is the possibility to power the connected devices with DC 5/12V and max. 300mA current consumption, and also the long operation time. Monitor is equipped with plastic housing.

Standard:	AHD - 1080p, HD-CVI - 1080p, HD-TVI - 3 Mpx, PAL, NTSC
Screen size:	4.3 "
Native resolution:	480 x 272 px
Contrast:	400 : 1
Brightness:	250 cd/m ²
Response time:	8 ms
Image adjustment:	Configurable: brightness, contrast, saturation
Video input:	 1 pcs - BNC cable included in the kit 1 pcs BNC socket
Audio input:	1 pcs RCA plug
Sleep function:	-
Main features:	 UTP cables or phone lines connecting test with RJ-45 connectors, DC 5V / 12V, max. 300mA power source, Flashlight built-in, The device has a practical storage compartment with a magnet
Battery power supply:	Li-Ion battery 3.7 V, 4000 mAh (included)



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Power supply:	5 V DC / 2 A (power adapter included)
Operation temp:	-30 °C 70 °C
Weight:	0.26 kg
Dimensions:	140 x 110 x 45 mm
Supported languages:	English, Chinese
Guarantee:	2 years

