

Code: LE-337223

## FLUSH-MOUNTING DISTRIBUTION CABINET 72-MODULAR **LE-337223** XL<sup>3</sup> S 160 LEGRAND

3-row 72-modular flush-mounting distribution electric cabinet.  
NOTE: Doors and terminal blocks must be ordered separately.



|                              |                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Method of mounting:          | Flush-mounted                                                                                                                                                                                                                                                                                                                                                                                              |
| Number of mounted modules:   | 24 x 3 rows                                                                                                                                                                                                                                                                                                                                                                                                |
| Spacing between TH 35 rails: | 150 mm                                                                                                                                                                                                                                                                                                                                                                                                     |
| Transparent door:            | (not included)                                                                                                                                                                                                                                                                                                                                                                                             |
| Main features:               | <ul style="list-style-type: none"> <li>• Easily adjustable depth of the TH 35 chassis</li> <li>• Large capacity</li> <li>• Monobloc housing</li> <li>• Flexibility in the selection of terminal blocks</li> <li>• Possibility of connecting the housings vertically</li> <li>• Max. current : 160 A</li> <li>• Short-circuit current : 17 kA</li> <li>• Equipped with faceplates at full height</li> </ul> |
| Equipment:                   | Faceplates : 1 x 3R                                                                                                                                                                                                                                                                                                                                                                                        |
| Material:                    | Steel                                                                                                                                                                                                                                                                                                                                                                                                      |
| Color:                       | White                                                                                                                                                                                                                                                                                                                                                                                                      |
| "Index of Protection":       | <ul style="list-style-type: none"> <li>• IP30 (without door)</li> <li>• IP40 (with door)</li> </ul>                                                                                                                                                                                                                                                                                                        |

|                            |                                                                                                  |
|----------------------------|--------------------------------------------------------------------------------------------------|
| IK rating:                 | <ul style="list-style-type: none"><li>• IK04 (without door)</li><li>• IK07 (with door)</li></ul> |
| Compliance with standards: | IEC/EN 61439-1, IEC/EN 61439-3, IEC 60695-2-1                                                    |
| Operation temp:            | -5 °C ... 40 °C                                                                                  |
| Weight:                    | 13.56 kg                                                                                         |
| Dimensions:                | 665 x 660 x 135 mm ,<br>595 x 590 x 135 mm - flush-mounting box                                  |
| Manufacturer / Brand:      | LEGRAND                                                                                          |
| Guarantee:                 | 2 years                                                                                          |