

Code: LE-601943

## SURFACE-MOUNTING HERMETIC DISTRIBUTION CABINET 36-MODULAR **LE-601943** RN65 LEGRAND



3-row 36-modular surface-mounting, hermetic distribution electric cabinet.

Method of mounting:	Surface
Number of mounted modules:	12 x 3 rows
Spacing between TH 35 rails:	150 mm
Transparent door:	✓
Main features:	<ul style="list-style-type: none"> <li>• Weatherproof cabinet</li> <li>• Fully reversible door and cabinet</li> <li>• Removable chassis and faceplates</li> <li>• The TH 35 rail with 2-position mounting for modular products</li> <li>• Can be fitted with perforated plates and solid faceplates for mounting non-modular products</li> <li>• Lockable door handle, sealable cover and faceplate</li> <li>• Rated voltage : 400 V AC, 50 / 60 Hz</li> <li>• Max. current : 90 A</li> <li>• Short-circuit current : 10 kA</li> <li>• Equipped with terminal blocks and modules blanking plates</li> </ul>
Equipment:	<ul style="list-style-type: none"> <li>• Terminal blocks</li> <li>1 x ( 21 x 1.5 ... 16 mm<sup>2</sup> + 1 x 6 ... 25 mm<sup>2</sup> )</li> <li>3 x ( 8 x 1.5 ... 16 mm<sup>2</sup> )</li> <li>• Module blanking plates : 2 x 5 pcs</li> </ul>





# DATA SHEET

Material:	Self-extinguishing
Color:	Light gray
"Index of Protection":	IP65
IK rating:	IK09
Complies with norms:	PN-EN 60439-3, IEC 60695-2-11, IEC 62262
Operation temp:	-25 °C ... 40 °C
Weight:	4.47 kg
Dimensions:	340 x 622 x 161 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years

