

Code: DS-7732NI-K4

NVR **DS-7732NI-K4** 32 CHANNELS Hikvision

The DS-7732NI-K4 digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



| | |
|----------------------------------|---|
| Standard: | TCP/IP |
| Supported resolutions: | 32 @ 3840 x 2160 px, 32 @ 3072 x 2048 px, 32 @ 2560 x 1920 px, 32 @ 2048 x 1536 px, 32 @ 1920 x 1080 px 32 @ 1600 x 1200 px 32 @ 1280 x 720 px 32 @ 704 x 576 px |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output |
| Audio support: | 32 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265 / H.264 / H.264+ / MPEG-4 |
| Maximal total frame rate: | 800 fps @ 3840 x 2160 px, 800 fps @ 3072 x 2048 px, 800 fps @ 2560 x 1920 px, 800 fps @ 2048 x 1536 px, 800 fps @ 1920 x 1080 px 800 fps @ 1600 x 1200 px 800 fps @ 1280 x 720 px 800 fps @ 704 x 576 px |
| Supported hard drives: | 4 x 6 TB SATA |
| Recording modes: | Manual, Sensor, Motion detection, Schedule |
| Network protocols: | TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, HTTPS, UPnP, iSCSI, Hik Cloud P2P |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |



DATA SHEET

| | |
|-------------------------------------|--|
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow |
| Bitrate: | max. 256 Mbps |
| Network functions: | <ul style="list-style-type: none">• Live image view, Playback the records, Backup the records• max. 128 on-line users - iVMS-4200 application• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its |
| Operation temp: | -10 °C ... 55 °C |
| ONVIF: | ✓ |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application iVMS-4500 or Hik-Connect• iOS (iPhone): Free application iVMS-4500 or Hik-Connect |
| Default IP address: | DHCP or 192.168.1.64 |
| Default admin user / password: | admin / - |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports: | 8000 |
| RTSP URL: | <ul style="list-style-type: none">• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |
| Alarm inputs / outputs: | 16 / 4 |
| PTZ control: | IP Speed Dome Cameras |
| Motion Detection: | ✓ |
| Intelligent image analysis: | ✓ |
| Mouse support: | ✓ |
| IR remote controller in the set: | ✓ |
| Power supply: | 100 ... 240 V AC |
| Weight: | 4.16 kg |
| Dimensions: | 440 x 390 x 75 mm |
| Supported languages: | English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Country of origin: | China |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 303603706 |
| Guarantee: | 3 years |

