

Code: DS-2CE56D8T-ITM(2.8mm)

## HD-TVI CAMERA **DS-2CE56D8T-ITM(2.8mm)** - 1080p Hikvision

Megapixel camera with Progressive Scan CMOS sensor and HD-TVI (High Definition Transport Video Interface).

The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases).



|                                  |                                                                                                                   |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Standard:                        | HD-TVI                                                                                                            |
| Sensor:                          | Progressive Scan CMOS                                                                                             |
| Matrix size:                     | 2.1 Mpx                                                                                                           |
| Resolution:                      | 1920 x 1080 - 1080p                                                                                               |
| Range of IR illumination:        | 20 m                                                                                                              |
| IR illuminator power adjustment: | Automatic                                                                                                         |
| Lens:                            | 2.8 mm / F1.4                                                                                                     |
| View angle:                      | <ul style="list-style-type: none"> <li>• 104 ° (manufacturer data)</li> <li>• 102 ° (our tests result)</li> </ul> |
| Video output:                    | 1 Vpp / 75 Ω - HD-TVI, BNC socket                                                                                 |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:         | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• Sense-UP - (Slow Shutter) - Increase the sensor sensitivity</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 4</li> <li>• Motion Detection - max. 4 zones</li> <li>• IR illuminator optimization</li> <li>• Mirror - Mirror image</li> <li>• BLC - Back Light Compensation</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul> |
| OSD menu:              | OSD menu available via Hikvision HD-TVI recorder                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Power supply:          | 12 V DC / 290 mA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Power consumption:     | ≤ 3.5 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Housing:               | Dome - Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Color:                 | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| "Index of Protection": | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Operation temp:        | -40 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Weight:                | 0.25 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Dimensions:            | Ø 91 x 68 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Supported languages:   | English                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Country of origin:     | China                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| SAP Code:              | 300609584                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Manufacturer / Brand:  | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Guarantee:             | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |