

Code: TR-1D-UHD*P2

VIDEO BALUN **TR-1D-UHD*P2**

The TR-1D-UHD*P2 is designed to video signal transmission via twisted-pair cable. It is important to pay attention to linking the adequate terminals: (+) and (-). Reverse connection would cause distortion of image.



In package:	2 pcs The price for package
Standard:	• AHD - 8 Mpx 4K UHD, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC
Device type:	Passive
Number of channels:	1
Video transmission range:	• 250 m @ 720p - UTP cat. 5e • 150 m @ 1080p - UTP cat. 5e • 400 m @ CVBS - PAL, NTSC - UTP cat. 5e
Attenuation:	• 4.43 MHz @ 0.34 dB • 11 MHz @ 0.52 dB • 21 MHz @ 0.73 dB • 38 MHz @ 1.15 dB • 42 MHz @ 1.39 dB • 67.5 MHz @ 2.00 dB The attenuation applies to two devices connected to each other
CMRR (dB @ 5MHz):	60 dB
Coaxial socket impedance:	75 Ω
Symmetrical socket impedance:	100 Ω
Coaxial socket type:	BNC Plug with cable
Symmetrical socket type:	Cable terminals
Operation temp:	-10 °C ... 70 °C
Permissible relative humidity:	< 95 %



DATA SHEET

Weight:	0.022 kg
Dimensions:	36.5 x 20 x 16 mm
Guarantee:	Lifetime warranty