

Code: DHI-VTO1220BW

VIDEO DOORPHONE **DHI-VTO1220BW** DAHUA



Video Doorphone is mounted in a flush-mounted housing.
ATTENTION! The device does not support the Dahua analogue system.

Sensor:	1/3 ", 1.3 Mpx CMOS
Lens:	3.6 mm
View angle:	95 °
Display:	3.5 " TFT LCD, 320 x 240 px
Image compression method:	H.264
LED illuminator:	✓
Compatibility:	DAHUA IP Protocol
RS-485:	✓
UTP category:	UTP cat. 5e
Main features:	• proximity reader built-in - 13.56 MHz S50, • Touch control keys, • LCD display, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface ,
Operation temp:	-40 °C ... 60 °C



DATA SHEET

Power supply:	12 V DC / 0.83 A
Power consumption:	≤ 10 W
Housing:	Tempered glass
Color:	White
"Index of Protection":	IP65
Weight:	1.09 kg
Dimensions:	408 x 150 x 77 mm
Supported languages:	English, Bulgarian, Czech, Finnish, Polish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

