

Code: ACAR-DIGITAL

POWER DISTRIBUTION UNIT **ACAR-DIGITAL** (5 OUTLETS)

Protection device, protects the devices against lightning discharges or surges in AC 230V power lines. The device is equipped with a system for monitoring the supply voltage and the total current, power and energy consumed by the receivers connected to the power outlets. The meter readings can be reset at any time.



Rated voltage:	230 V AC / 50 Hz
Protection level:	≤ 1.3 kV
Nominal load current:	10 A (total)
Maximal load power:	2300 W
Nominal stroke current:	2 kA (L/N) - 8/20 μs
Maximum stroke current:	6.5 kA (L/N) - 8/20 μs
Leak current:	< 0.5 mA
Automatic delayed fuse:	✓
Response time:	< 25 ns
Number of outlets:	5 grounded outlets 16A/250V - (Schuko)
Switch:	Two-way switch - with light indication
Main features:	<ul style="list-style-type: none"> • Easily readable LCD with backlight displaying detailed information on system state, • Supply voltage measurement : 80 V ... 250 V @ 50Hz, • Supply current measurement : 0.01 A ... 10 A @ 50/60 Hz, • Power measurement : 1 W ... 2500 W, • Energy measurement : 1 Wh ... 9999 Wh • Energy meter reset • Setting the alarm after exceeding the power consumption
Length of the cable:	3 m
Housing:	Plastic - non-flammable
Weight:	0.65 kg
Dimensions:	447 x 57 x 43 mm



DATA SHEET

Guarantee:	2 years
------------	---------