

Code: CS-H8-70H

MULTI-FUNCTIONAL CCTV TESTER **CS-H8-70H**

Multi-functional tester of AHD, HD-CVI, HD-TVI, IP cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system.



Video standard:	<ul style="list-style-type: none"> • AHD - 5 Mpx, • HD-CVI - 8 Mpx, • HD-TVI - 8 Mpx, • TCP/IP - 4K, • CVBS - PAL / NTSC
Display:	7 " Retina - capacitive touch screen, 1920 x 1200 px
Video input:	<ul style="list-style-type: none"> • 1 pcs AHD / HD-CVI / HD-TVI / CVBS - BNC socket • 1 pcs HDMI
Video output:	<ul style="list-style-type: none"> • 1 pcs CVBS - BNC socket • 1 pcs HDMI
Port LAN:	2 pcs - PoE cameras and switches support
Audio input:	1 pcs Mini Jack
Audio output:	1 pcs Mini Jack
Video signal level meter:	PAL / NTSC only
Video signal generator:	<ul style="list-style-type: none"> • Test signal generator • Generating eight color bars in PAL / NTSC standards • It is possible to generate a blue or black screen
Serial ports:	RS-485
Protocols:	Support for over 30 RS485 protocols : Pelco-D, Pelco-P, YAAN, YAAN-O, YAAN-1, SAMSUNG, PANASONIC, Lilin-FAST, Lilin-MLP2, MOLYNX, MINKING A01, Fastrax, CBC, LC-NEW, WV-CS850, SONY-EVI, LG-MULTIX, DAT-SD, VICON, Vcltp, DH-YTC 06, Santachi, Bosch OSRD, TeleEye DM2, HD 600, Hikvision, KALATEL ASC, AD 168(M-B), SAMSUNG SPD, Siemens, Cohu, MINKING B01, ALEC



DATA SHEET

Baud rates:	150, 300, 600, 1200, 2400, 4800, 9600, 19200, 38400, 115200 b/s
LAN (twisted-pair) or telephone cables testing:	UTP cables or phone lines connecting test with RJ-45 connectors
RS-485, RS-232 lines test:	Data analysis from control device (the commands are displayed in hexadecimal)
Wi-Fi module:	✓
Identification the wire in the group of wires:	✓
Audio test:	✓
Digital multimeter:	—
Optical power measurement:	—
VLS (VFL) - Visual Fault Locator of fiber cable:	—
TDR reflectometer:	Detecting and locating a cable break (UTP only)
Operation as power source:	<ul style="list-style-type: none">• 12 V DC / 3 A• 5 V DC / 2 A from USB port• 24 V DC / 2 A (screw terminals)• 48 V (PoE, LAN), 24 W
Battery power supply:	<ul style="list-style-type: none">• Battery 7800 mAh• 12 V DC / 2 A (power adapter included)
Estimated battery operation time:	max. 10 hours
Operation:	Graphical menu - touch control and by using the buttons
Main features:	<ul style="list-style-type: none">• AHD cameras test• HD-CVI cameras test• HD-TVI cameras test• PAL/NTSC cameras test• IP cameras test - Supported image compression methods : H.265, H.264, MJPEG• Searching and view of IP cameras compatible with Onvif• Motor units and PTZ (Speed Dome) cameras control• IP cameras view from embedded applications - CloudSEE, gDMSS HD Lite, Fseye, XMEye, gDMSS Lite, EZView, FreeIP PRO, iVMS-4500 HD, MEye• Embedded Internet browser - Google Chrome• Test signal generator• LAN connections monitoring• IP addresses scanner• PING - test the link using ICMP packets• Detection of the connected port in switch• LAN (twisted-pair) cables testing• PoE cameras and switches support• PoE power meter• DC 5V / 12V / 48V power source• Data monitor - serial port data analysis RS-485• Audio test• Wi-Fi network analyzer• Hotspot - Wi-Fi• Video recording to micro SD card with playback possibility - 8 GB included• Playback the records• Calculator• Flashlight built-in• Illuminated buttons
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	0.97 kg



DATA SHEET

Dimensions:	262 x 161 x 45 mm
Supported languages:	Polish, English, Czech, French, Spanish, German, Portuguese, Russian, Serbian, Turkish, Italian
Guarantee:	2 years

