

Code: DS-2CE56D0T-IRMMF(3.6mm)

## AHD, HD-CVI, HD-TVI, PAL CAMERA **DS-2CE56D0T-IRMMF(3.6mm)** - 1080p Hikvision

Megapixel camera with Progressive scan CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The change of the AHD / HD-CVI / HD-TVI / PAL standard is done with the corresponding button by keeping it pressed for approx. 5 seconds.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



Standard:	AHD / HD-CVI / HD-TVI / PAL
Sensor:	Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Lens:	3.6 mm
View angle:	<ul style="list-style-type: none"> <li>• 82 ° (manufacturer data)</li> <li>• 78 ° (our tests result)</li> </ul>
IR illuminator support:	ICR - Movable InfraRed filter
S/N ratio:	> 62 dB
Video output:	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI, BNC socket

Main features:	<ul style="list-style-type: none"><li>• DNR - Digital Noise Reduction</li><li>• ICR - Movable InfraRed filter</li><li>• AGC - Automatic Gain Control</li><li>• Day/night mode</li><li>• BLC - Back Light Compensation</li><li>• Auto White Balance</li></ul>
OSD menu:	—
Power supply:	12 V DC / 330 mA
Power consumption:	≤ 4 W
Housing:	Dome, Plastic
Color:	White
Vandal-proof:	—
"Index of Protection":	IP44
Operation temp:	-20 °C ... 45 °C
Weight:	0.15 kg
Dimensions:	Ø 98 x 66 mm
Manufacturer / Brand:	Hikvision
SAP Code:	300609197
Guarantee:	<b>3 years</b>