

Code: DS-3E1326P-E

Switch PoE **DS-3E1326P-E** 24-PORT + 2 x SFP Hikvision

The DS-3E1326P-E switch is designed for large streams of video data in the CCTV IP surveillance networks.
Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> • 2 x port Combo: SFP (Base-X) / RJ45 (Base-T) • 24 x RJ45 10/100 Base-T (24 x PoE (802.3af/at))
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 Mbps - 24 LAN & PoE ports • 10 / 100 / 1000 Mbps - 2 Uplink ports • 1000 Mbps - 2 SFP ports
Maximal output power:	30 W / port PoE
Maximal total power:	370 W
MAC addresses table:	4k
Management:	✓
Default IP address:	192.168.0.1
Default admin user / password:	admin / admin
Operation modes:	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Main features:	<ul style="list-style-type: none"> • IEEE 802.1Q VLAN • Half Duplex / Full Duplex • IGMP Snooping, IGMP v1 / v2 • The ability to assign MAC addresses to the port • IEEE 802.1x port authentication • Upload and download configuration file • protection against lightning discharges and voltage differences and strokes between devices • QoS
LED diodes:	Power, Link/Act, Run, PoE Max
Certificates:	CE
Power supply:	100 ... 240 V AC
Operation temp:	0 °C ... 40 °C
Weight:	4.28 kg
Dimensions:	440 x 290 x 43 mm
Manufacturer / Brand:	Hikvision



DATA SHEET

SAP Code:	301800860
Guarantee:	3 years