

Code: PRT66MF-G

PROXIMITY READER **PRT66MF-G** ROGER

Outdoor proximity cards and key-fobs reader. 13.56 MHz S50 standard.



Cards support:	13.56 MHz S50
Reading distance of prox-keys:	max. 6 cm
Keyboard built-in:	—
Communication:	<ul style="list-style-type: none"> • Wiegand 26-66bit, • Magstripe (Clock & Data), • RACS (Roger)
Main features:	<ul style="list-style-type: none"> • Autonomous operation or as terminal for the controller • Can be used for 13.56 MHz S50 card programming (free of charge RARC software is required) • Tamper protection (detection of removing from mounting surface and enclosure opening) • Manual or computer programming • Tamper protection (detection of removing from mounting surface and enclosure opening) • LED indication • Beep signal • Two transistor outputs • Two inputs NO/NC
Selected features of the standalone mode:	<ul style="list-style-type: none"> • 120 indexed users • History of 1024 events • Two way door control (requires using two readers of PRT series) • Operation with XM-2 I/O extension module (Full Standalone Mode)



DATA SHEET

Power supply:	12 V DC
Average current consumption:	65 mA
Operation temp:	-25 °C ... 60 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
Weight:	0.15 kg
Dimensions:	85 x 85 x 27 mm
Manufacturer / Brand:	ROGER
Guarantee:	3 years