

Code: AT-UPS1200-LED

UPS **AT-UPS1200-LED** 1200 VA EAST

The AT-UPS1200-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.
The device works with power supply adapters having Active Power Factor Correction (APFC).



Nominal power:	720 W
Apparent Power:	1200 VA
Input voltage:	165 V ... 275 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	2 ... 7 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	2 pcs - 12V/7Ah
Estimated battery operation time:	<ul style="list-style-type: none"> • 57 minutes @ 100 W, • 14 minutes @ 300 W, • 8 minutes @ 500 W
Number of outputs:	3 pcs CEE 7/3 (Schuko)



DATA SHEET

Protections:	<ul style="list-style-type: none">• Fuse• Overvoltage• Overload protection• Overcharge protection• Telephone line filter
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling
Main features:	<ul style="list-style-type: none">• Auto restart while AC is recovering• Automatic Voltage Regulator (AVR)• Compatible with power generators• Remote management - UPSmart application included• Built-in EMI, RFI filter• Configurable alarm
Application:	<ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	10.17 kg
Dimensions:	330 x 227 x 125 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years