

Code: DS-KB8112-IM

## VIDEO DOORPHONE **DS-KB8112-IM** Hikvision

The device cooperates with video doorphones, and other panels working in Hikvision IP standard.



Sensor:	1/3 " CMOS, 720p
LED illuminator:	—
IR illuminator:	✓ 940 nm (invisible to the human eye), Range : 5 m
Compatibility:	Hikvision IP Video Doorphones
proximity reader built-in:	—
UTP category:	UTP cat. 5e
Alarm inputs:	1 pcs
Relay outputs:	1 pcs NO/NC
RS-485:	—
Ethernet:	1 x RJ-45 - 10/100 Base-T

Main features:	<ul style="list-style-type: none"><li>• D-WDR - Wide Dynamic Range,</li><li>• Motion Detection ,</li><li>• Configurable: brightness, contrast, saturation</li><li>• Microphone built-in,</li><li>• Speakers built-in,</li><li>• Bidirectional communication,</li><li>• The device has the ability to work with the <a href="#">Hik-Connect</a> application for mobile devices, without the use of an internal panel</li></ul>
Operation temp:	-30 °C ... 50 °C
Power supply:	<ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 1 A</li></ul>
Housing:	Metal, Waterproof, Vandal-proof - IK09
"Index of Protection":	IP66
Color:	Black
Weight:	0.79 kg
Dimensions:	162 x 74 x 54 mm
Supported languages:	English
Manufacturer / Brand:	Hikvision
SAP Code:	305300432
Guarantee:	<b>3 years</b>