DATA SHEET

Code: DS-K2802

ACCESS CONTROLLER **DS-K2802** Hikvision

The DS-K2802 controller is intended to use in access control systems based on electrical control of door opening.



Number of supported readers:	4 pcs @ Wiegand
Battery backup support:	–
Input lines:	2 pcs - Alarm inputs , 2 pcs - Reed switch , 2 pcs - Door/gate opening button
Output lines:	2 pcs - Lock relay , 2 pcs - Relay
Communication:	• Ethernet, • Wiegand
Power supply:	230 V AC
Main features:	• 10 000 indexed users • History of 50 000 events • Remote programming from PC • Metal housing
Operation temp:	-20 °C ... 65 °C
Permissible relative humidity:	10 % ... 95 % (non-condensing)
Weight:	2.32 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Dimensions:	285 x 235 x 90 mm
Manufacturer / Brand:	Hikvision
SAP Code:	302901272
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60