

Code: APTI-N0901-4P-M5

## NVR **APTI-N0901-4P-M5** 9 CHANNELS + 4-PORT POE SWITCH

The APTI-N0901-4P-M5 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

**Attention!** The built-in PoE switch only supports APTI cameras.



|                                     |                                                                                                                                                                                                                                                                              |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                           | TCP/IP                                                                                                                                                                                                                                                                       |
| Supported resolutions:              | max. 5 Mpx - 2592 x 1944 px                                                                                                                                                                                                                                                  |
| Video outputs:                      | 1 pcs HDMI<br>1 pcs VGA                                                                                                                                                                                                                                                      |
| Audio support:                      | 9 Channels - Audio from cameras                                                                                                                                                                                                                                              |
| Audio inputs:                       | —                                                                                                                                                                                                                                                                            |
| Audio outputs:                      | 1 pcs CINCH                                                                                                                                                                                                                                                                  |
| Image compression method:           | H.265, H.264                                                                                                                                                                                                                                                                 |
| Supported hard drives:              | 1 x 6 TB SATA                                                                                                                                                                                                                                                                |
| Recording modes:                    | Manual, Motion Detection, Schedule                                                                                                                                                                                                                                           |
| Network protocols:                  | ONVIF, Private                                                                                                                                                                                                                                                               |
| External storage devices backup:    | Records backup at (.avi) format to USB (pendrive)                                                                                                                                                                                                                            |
| Searching and playback the records: | Records searching: timeline or file list. Playback: forward, fast<br>Playback max. 4 cameras in the same time @ 1080p                                                                                                                                                        |
| Bitrate:                            | 60 Mbps                                                                                                                                                                                                                                                                      |
| Network functions:                  | Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters                                                                                                                                              |
| ONVIF:                              | ✓                                                                                                                                                                                                                                                                            |
| Mobile phones support:              | Port no.: 554 or access by a cloud (P2P)<br>• Android: Free application <a href="#">FREEIP PRO</a> , Android: Free application <a href="#">FREEIP</a><br>• iOS (iPhone): Free application <a href="#">FREEIP PRO</a> , iOS (iPhone): Free application <a href="#">FREEIP</a> |



# DATA SHEET

|                                  |                                                                                                                     |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Default admin user / password:   | admin / 12345                                                                                                       |
| Default IP address:              | 192.168.1.88                                                                                                        |
| Web browser access ports:        | 80, 5000, 554                                                                                                       |
| PC client access ports:          | 80, 5000, 554                                                                                                       |
| Mobile client access ports:      | 80, 5000, 554                                                                                                       |
| Alarm inputs / outputs:          | —                                                                                                                   |
| PTZ control:                     | IP Speed Dome Cameras                                                                                               |
| Motion Detection:                | Split the screen into zones : 24 x 18 motion zones                                                                  |
| USB:                             | 2 pcs USB 2.0                                                                                                       |
| Mouse support:                   | ✓                                                                                                                   |
| IR remote controller in the set: | —                                                                                                                   |
| Switch PoE:                      | 4-port PoE Switch built-in : 13 W / Channel - IEEE 802.3af                                                          |
| Operation temp:                  | -10 °C ... 55 °C                                                                                                    |
| Power supply:                    | 48 V DC / 1.25 A                                                                                                    |
| Weight:                          | 0.55 kg                                                                                                             |
| Dimensions:                      | 220 x 218 x 55 mm                                                                                                   |
| Supported languages:             | English, Bulgarian, Czech, French, Greek, Spanish, German, Polish, Portuguese, Russian, Turkish, Hungarian, Italian |
| Country of origin:               | China                                                                                                               |
| Manufacturer / Brand:            | APTI                                                                                                                |
| Guarantee:                       | 2 years                                                                                                             |