DATA SHEET

Code: DHI-NVR608R-128-4KS2

NVR **DHI-NVR608R-128-4KS2** 128 CHANNELS +eSATA DAHUA



Standard:	TCP/IP
Supported resolutions:	max. 12 Mpx - 4000 x 3000 px
Video outputs:	2 pcs HDMI 1 pcs VGA
Audio support:	128 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH - Microphone
Audio outputs:	1 pcs - CINCH
Image compression method:	H.265 / H.264 / MJPEG
Supported hard drives:	8 x 8 TB SATA + 1 x eSATA Operation modes : SINGLE, Raid 0/1/5/10
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search ONVIF 2.4
External storage devices backup:	Backup to USB drive (pendrive, external drive) - 2 x Port USB 3.0
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function
Bitrate:	max. 384 Mbps (total)
Power consumption:	≤ 20 W (without HDD)
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users
ONVIF:	2.4

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address:	192.168.1.108
Default admin user / password:	admin / admin
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	16 pcs / 8 pcs
PTZ control:	RS-485 - Many protocols IP Speed Dome Cameras
Motion Detection:	22 x 18 motion zones
Intelligent Image Analysis:	• intrusion, crossing the line (tripwire), abandoned/missing object, people counting, heat map • Heat map - the selection in the image by corresponding colors the areas with different traffic
USB:	2 pcs USB 3.0 2 pcs USB 2.0
Mouse support:	✔
IR remote controller in the set:	–
Main features:	• Ability to work drives in a RAID array can significantly improve system reliability • Redundant power supply - The recorder has been equipped with two separate power supply adapters
Power supply:	100 V ... 240 V AC
Weight:	8.9 kg (without HDD)
Dimensions:	444 x 475 x 95 mm
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	DAHUA
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60