

Code: KN-CA52D

## GATE MAGNETIC DETECTOR **KN-CA52D**

The magnetic contacts can be used wherever required for controlling the status of doors, windows and/or other movable elements, e.g. for protection or monitoring of access to particular sites, spaces, facilities, in automatic control systems, etc.  
The contact is designed for surface mounting.



|                                |                                                                                                                                                                                                                                                                                                                         |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Detection:                     | Opening the door or window                                                                                                                                                                                                                                                                                              |
| Maximum reed switched voltage: | 20 V                                                                                                                                                                                                                                                                                                                    |
| Maximal switched current:      | 10 mA                                                                                                                                                                                                                                                                                                                   |
| Make distance:                 | 19 mm                                                                                                                                                                                                                                                                                                                   |
| Break distance:                | 20 mm                                                                                                                                                                                                                                                                                                                   |
| Main features:                 | <ul style="list-style-type: none"> <li>• Rugged, metal sealed body</li> <li>• NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed</li> <li>• Length of the cables : 40 cm</li> <li>• The cables are protected with a metal spiral tube with a length of 36.5 cm</li> </ul> |
| Color:                         | Silver                                                                                                                                                                                                                                                                                                                  |
| Weight:                        | 0.12 kg (total)                                                                                                                                                                                                                                                                                                         |
| Dimensions:                    | 49 x 19.5 x 9.8 mm                                                                                                                                                                                                                                                                                                      |
| Guarantee:                     | 2 years                                                                                                                                                                                                                                                                                                                 |