

DATA SHEET

Code: S601A-2

VIDEO DOORPHONE **S601A-2** VIDOS

Video Doorphone is mounted in a flush-mounted housing. Surface mounting is possible with the D600B3 cover. Built-in RFID reader allows to control the electric strike using key fobs, proximity cards and tags functioning in the Unique EM $125 \mathrm{kHz}$ standard.

The S601A-2 is designed to cooperation with video doorphones and panels working in analog VIDOS system.



| Compatibility: | VIDOS Analog Video Doorphones |
|-----------------------------------|--|
| Sensor: | 1/3 " 600 TVL |
| View angle: | 87 ° |
| IR illuminator: | ✓ |
| LED illuminator: | _ |
| proximity reader built-in: | Standard - Unique EM 125kHz |
| Fingerprint reader built-in: | |
| Built-in keypad: | - |
| The number of subscribers served: | 1 |
| Video output: | compatible with VIDOS analog video door-phone system |



DATA SHEET

| Main features: | 2 zones support Number of supported proximity cards: max. 1010 Adjustment of the opening time of the electric strike: 1s 99s Electric strikes and electromagnetic locks support Output for the additional lock release button Possibility of working in bistable mode (close-up of the card releases the electric strike, re-closing closes it) Vandal-proof front panel Illuminated button and signboard for the surname |
|------------------------|---|
| Power supply: | 12 V DC 15 V DC |
| Power consumption: | ≤ 1.5 W (operation) |
| Housing: | Acid-proof steel / Plastic, Waterproof |
| Color: | Silver |
| "Index of Protection": | IP65 |
| Operation temp: | -20 °C 55 °C |
| Weight: | 0.6 kg |
| Dimensions: | 195 x 100 x 55 mm |
| Manufacturer / Brand: | VIDOS |
| Guarantee: | 3 years |