

Code: S1104A

## VIDEO DOORPHONE **S1104A** VIDOS

Video Doorphone is mounted in a surface housing. The S1104A is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



Compatibility:	VIDOS DUO
Sensor:	1/2.7", 600 TVL
View angle:	105 °
IR illuminator:	—
LED illuminator:	✓
proximity reader built-in:	Standard : Unique EM 125kHz
The number of subscribers served:	4
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	<ul style="list-style-type: none"> <li>• Wiring - 2 wires without polarity</li> <li>• Relay output : 1 pcs or 2 pcs - B5 Module</li> <li>• PIR detectors support</li> <li>• Permanent or cyclical zoom-up of the observed image</li> <li>• Electric strikes and electromagnetic locks support</li> <li>• Electric lock supply: 12V DC / max. 300mA</li> <li>• Easy to add and delete users via MASTER key fobs</li> <li>• Call start and lock opening indicator</li> </ul>
Power supply:	24 V DC



# DATA SHEET

Power consumption:	≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Weight:	0.62 kg
Dimensions:	180 x 95 x 42 mm
Manufacturer / Brand:	VIDOS
Guarantee:	<b>3 years</b>