

Code: S561A

VIDEO DOORPHONE **S561A** VIDOS

Video Doorphone is mounted in a flush-mounted housing. Surface mounting is possible with the D561B cover. Built-in RFID reader allows to control the electric strike using key fobs, proximity cards and tags functioning in the Unique EM 125kHz standard. The S561A is designed to cooperation with video doorphones and panels working in analog VIDOS system.



| | |
|-----------------------------------|--|
| Compatibility: | VIDOS Analog Video Doorphones |
| Sensor: | 1/3 " 600 TVL |
| View angle: | 87 ° |
| IR illuminator: | ✓ |
| LED illuminator: | — |
| proximity reader built-in: | Standard - Unique EM 125kHz |
| Fingerprint reader built-in: | — |
| Built-in keypad: | — |
| The number of subscribers served: | 1 |
| Video output: | compatible with VIDOS analog video door-phone system |

| | |
|------------------------|---|
| Main features: | <ul style="list-style-type: none">• The kit includes a MASTER card that allows you to add user cards yourself• Number of supported proximity cards : max. 1000• Adjustment of the opening time of the electric strike: 1s ... 99s• Electric strikes and electromagnetic locks support• Output for the additional lock release button• Vandal-proof front panel• Illuminated buttons and signboard for the surname |
| Power supply: | 12 V DC ... 15 V DC |
| Power consumption: | ≤ 1.5 W (operation) |
| Housing: | Acid-proof steel / Plastic, Waterproof |
| Color: | Silver |
| "Index of Protection": | IP65 |
| Operation temp: | -20 °C ... 55 °C |
| Weight: | 0.87 kg |
| Dimensions: | 250 x 120 x 51 mm |
| Manufacturer / Brand: | VIDOS |
| Guarantee: | 3 years |