DATA SHEET

Code: S1500DLC

VIDEO DOORPHONE **S1500DLC** VIDOS



Video Doorphone is mounted in a flush-mounted housing. The S1500DLC is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.

Compatibility:	VIDOS DUO
Sensor:	1/2.7 " Fish Eye CMOS, 600 TVL
View angle:	105 °
IR illuminator:	–
LED illuminator:	✓
proximity reader built-in:	–
Built-in keypad:	✓
The number of subscribers served:	32
Video output:	compatible with the VIDOS DUO digital video doorphone system

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Main features:	• Fisheye lens • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 module • Touch and backlit keyboard buttons • Connector for the additional exit button • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 280mA • DIP SWITCH for configuration and addressing • Window with device operation status indicators • Built-in multifunctional LCD performing the function of an electronic list of tenants and an information panel
Power supply:	26 V DC
Power consumption:	≤ 5 W (operation) ≤ 1 W (Standby mode)
Housing:	Acid-proof steel / Plastic, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C ... 55 °C
Weight:	1.17 kg
Dimensions:	316 x 133 x 48 mm
Manufacturer / Brand:	VIDOS
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60