

Code: RS-108

## SWITCH POE TO RACK CABINET **RS-108** 10-PORT PULSAR

The RS-108 PoE Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 Mbps. PoE/PoE+ powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.  
The device is mounted to RACK 19" cabinet.



|                       |                                                                                                                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"> <li>• 8 x RJ45 ( 8 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 - Uplink</li> </ul>                                                                                                             |
| Management:           | —                                                                                                                                                                                                                               |
| LED diodes:           | Power, PoE, Link/Act                                                                                                                                                                                                            |
| Transmission speed:   | 10 / 100 Mbps - 8 x LAN & PoE ports<br>10 / 100 Mbps - 2 x Uplink ports                                                                                                                                                         |
| Maximal output power: | 30 W / port PoE+                                                                                                                                                                                                                |
| Maximal total power:  | 96 W                                                                                                                                                                                                                            |
| MAC addresses table:  | 1k                                                                                                                                                                                                                              |
| Main features:        | <ul style="list-style-type: none"> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• (RJ45) 10/100 Mb Auto-Negotiation, Auto MDI/MDIX</li> <li>• Industrial wide temperature design.</li> </ul> |
| Certificates:         | CE                                                                                                                                                                                                                              |
| Power supply:         | 230 V AC                                                                                                                                                                                                                        |
| Housing:              | Steel - powder painted                                                                                                                                                                                                          |
| Color:                | Black (RAL 9005)                                                                                                                                                                                                                |
| Housing type:         | RACK 19", 1U                                                                                                                                                                                                                    |
| Operation temp:       | -20 °C ... 60 °C                                                                                                                                                                                                                |
| Weight:               | 2.7 kg                                                                                                                                                                                                                          |
| Dimensions:           | 482 x 227 x 44 mm                                                                                                                                                                                                               |
| Manufacturer / Brand: | PULSAR                                                                                                                                                                                                                          |



# DATA SHEET

Guarantee:

2 years