

Code: S1201A-SKP

VIDEO DOORPHONE INTEGRATED WITH MAILBOX **S1201A-SKP** VIDOS

Video doorphone integrated with one-way mailbox. The box is designed for mounting in a fence post or wall. Thanks to the use of the highest quality materials, it is resistant to weather conditions.

The video doorphone has been equipped with a color camera with the possibility of adjusting horizontally and vertically in the range of several degrees.

The S1201A-SKP is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.



| | |
|-----------------------------------|--|
| Compatibility: | VIDOS DUO |
| Sensor: | 1/2.7 " Fish Eye CMOS, 2 Mpx |
| View angle: | 170 ° |
| IR illuminator: | — |
| LED illuminator: | ✓ |
| proximity reader built-in: | Standard : Unique EM 125kHz |
| Built-in keypad: | — |
| Fingerprint reader built-in: | — |
| The number of subscribers served: | 1 |
| Video output: | compatible with the VIDOS DUO digital video doorphone system |

| | |
|------------------------|---|
| Main features: | <ul style="list-style-type: none"> • Integrated mailbox - Through • Wiring - 2 wires without polarity • Relay output : 1 pcs or 2 pcs - B5 module • Support up to 13 indoor devices (monitors / uniphones) • PIR detectors support • Permanent or cyclical zoom-up of the observed image • Electric strikes and electromagnetic locks support • Electric lock supply: 12V DC / max. 300mA • Easy to add and delete users via MASTER key fobs |
| Power supply: | 24 V DC |
| Power consumption: | <ul style="list-style-type: none"> ≤ 3 W (operation) ≤ 0.8 W (Standby mode) |
| Housing: | Acid-proof steel, Waterproof |
| Color: | Silver |
| "Index of Protection": | IP65 |
| Operation temp: | -20 °C ... 55 °C |
| Weight: | 4.78 kg |
| Dimensions: | <ul style="list-style-type: none"> • Front panel : 285 x 385 mm • Rear panel : 265 x 360 mm • Adjustable depth of the box : 190 ... 255 mm |
| Manufacturer / Brand: | VIDOS |
| Guarantee: | 3 years |