

## DATA SHEET

## Code: S1201A-SKM

## VIDEO DOORPHONE INTEGRATED WITH MAILBOX S1201A-SKM VIDOS



Video doorphone integrated with one-way mailbox. The box is designed for mounting in a fence post or wall. Thanks to the use of the highest quality materials, it is resistant to weather conditions.

The video doorphone has been equipped with a color camera with the possibility of adjusting horizontally and vertically in the range of several degrees.

The S1201A-SKM is dedicated for cooperation with video doorphones and panels compatible with the VIDOS DUO digital system.

Compatibility:	VIDOS DUO
Sensor:	1/2.7 " Fish Eye CMOS, 2 Mpx
View angle:	170 °
IR illuminator:	-
LED illuminator:	✓
proximity reader built-in:	Standard : Unique EM 125kHz
Built-in keypad:	-
Fingerprint reader built-in:	-
The number of subscribers served:	1
Video output:	compatible with the VIDOS DUO digital video doorphone system
Main features:	<ul> <li>Integrated mailbox - Through</li> <li>Wiring - 2 wires without polarity</li> <li>Relay output : 1 pcs or 2 pcs - B5 module</li> <li>Support up to 13 indoor devices (monitors / uniphones)</li> <li>PIR detectors support</li> <li>Permanent or cyclical zoom-up of the observed image</li> <li>Electric strikes and electromagnetic locks support</li> <li>Electric lock supply: 12V DC / max. 300mA</li> <li>Easy to add and delete users via MASTER key fobs</li> </ul>



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

S1201A-SKM



## DATA SHEET

Power supply:	24 V DC
Power consumption:	≤ 3 W (operation) ≤ 0.8 W (Standby mode)
Housing:	Acid-proof steel, Waterproof
Color:	Silver
"Index of Protection":	IP54
Operation temp:	-20 °C 55 °C
Weight:	4.45 kg
Dimensions:	<ul> <li>Front panel : 285 x 332 mm</li> <li>Rear panel : 260 x 112 mm</li> <li>Adjustable depth of the box : 260 410 mm</li> </ul>
Manufacturer / Brand:	VIDOS
Guarantee:	3 years

