

Code: BU650E-FR/UPS

UPS **BU650E-FR/UPS** 650 VA CyberPower

The BU650E-FR/UPS UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.



Nominal power:	360 W
Apparent Power:	650 VA
Input voltage:	165 V ... 280 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	4 ms (typical)
Charging time (recover to 90% capacity):	8 hours
Battery:	1 pcs - 12V/7Ah
Estimated battery operation time:	<ul style="list-style-type: none"> • 30 minutes @ 60 W, • 18 minutes @ 90 W
Number of outputs:	3 pcs
Protections:	<ul style="list-style-type: none"> • Glass Fuse • Overvoltage • Overload protection • Overcharge protection
Operation state indication:	<ul style="list-style-type: none"> • LED diodes, • Sound signaling



DATA SHEET

Main features:	<ul style="list-style-type: none">• Auto restart while AC is recovering• Automatic Voltage Regulator (AVR)• Compatible with power generators• Built-in EMI, RFI filter
Application:	<ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment
Housing type:	Desktop
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	3.72 kg
Dimensions:	240 x 92 x 158 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years

