

Code: DS-2CE56H0T-IT3ZF(2.7-13.5MM)

AHD, HD-CVI, HD-TVI, CVBS CAMERA **DS-2CE56H0T-IT3ZF(2.7-13.5MM)** - 5 Mpx Hikvision

Megapixel camera with Progressive scan CMOS sensor and AHD / HD-CVI / HD-TVI / CVBS. The change of the AHD / HD-CVI / HD-TVI / CVBS standard is done with the corresponding button by keeping it pressed for approx. 5 seconds.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

Housing construction allows to mount the camera to the ceiling and the wall (image is right oriented in both cases). In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals. Camera is according to IP67 Index of Protection norm.



| | |
|----------------------------------|--|
| Standard: | AHD, HD-CVI, HD-TVI, CVBS |
| Sensor: | Progressive Scan CMOS |
| Matrix size: | 5 Mpx |
| Resolution: | 2560 x 1944 - 5 Mpx @ 20 fps , 2560 x 1440 - 4 Mpx @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ 25 fps, 30 fps |
| Range of IR illumination: | 40 m |
| IR illuminator power adjustment: | Automatic |
| Lens: | 2.8 ... 13.5 mm - Motozoom |
| View angle: | 96 ° ... 29 ° |
| Video output: | 1 x AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω, BNC socket |

| | |
|------------------------|--|
| Main features: | <ul style="list-style-type: none"> • Motozoom lens • 2D-DNR - Digital Noise Reduction • D-WDR - Wide Dynamic Range • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Mirror - Mirror image • Sharpness - sharper image outlines |
| OSD menu: | ✓ |
| Power supply: | 12 V DC / 520 mA |
| Power consumption: | ≤ 6.3 W |
| Housing: | Dome, Metal |
| Color: | White |
| "Index of Protection": | IP67 |
| Operation temp: | -40 °C ... 60 °C |
| Weight: | 0.6 kg |
| Dimensions: | 134 x 124 x 111 mm |
| Supported languages: | English |
| Country of origin: | China |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 300611061 |
| Guarantee: | 3 years |