

DATA SHEET

Code: DS-KB6403-WIP

WIRELESS DOORBELL **DS-KB6403-WIP** Wi-Fi / IP Hikvision

The DS-KB6403-WIP Wi-Fi wireless doorbell enables, among others preview from built-in camera and bidirectional voice communication from mobile device level with the Hik-Connect application installed. When the bell button is pressed, the application displays a notification on the phone's screen.

The doorbell also has a motion detection function with the ability to local save short videos on the Micro SD card.

Attention! Access to the device's functions is possible only through the **Hik-Connect** application available on mobile devices with Android, iOS systems. The device does not have the ability to control the opening of the gate.



Sensor:	CMOS, 2 Mpx
Resolution:	1920 x 1080 640 x 480
Camera view angle:	180 °
IR illuminator:	✓
LED illuminator:	-
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11bg
Network interface:	Wi-Fi
Mobile phones support:	Android: Free application <u>Hik-Connect</u> iOS (iPhone): Free application <u>Hik-Connect</u>
Video format:	H.264
Supported audio formats:	G.711



DATA SHEET

Main features:	 Micro SD memory cards up to 128GB support (possible local recording), Motion Detection, Bidirectional communication, Full support via network: WiFi
Mount:	Surface-mounted
Power supply:	12 V DC / 600 mA (max)
Power consumption:	≤ 7.2 W
Housing:	Plastic, 4 replaceable panels in different colors included in the set
Color:	Black / Graphite / Silver / White
"Index of Protection":	IP54
Operation temp:	-30 °C 50 °C
Weight:	0.14 kg
Dimensions:	122 x 45 x 24 mm
Manufacturer / Brand:	Hikvision
SAP Code:	305300825
Guarantee:	3 years