

Code: UT850EG-FR/UPS

UPS **UT850EG-FR/UPS** 850 VA CyberPower

The UT850EG-FR/UPS UPS is a professional device used to maintain the operation of the components connected to it. The UPS UT CyberPower series has been equipped with the best-in-class housing of fireproof plastic, which provides outstanding fire resistance and helps to minimize possible losses in the case of fire.



| | |
|-----------------------------------|--|
| Nominal power: | 425 W |
| Apparent Power: | 850 VA |
| Input voltage: | 165 V ... 290 V AC |
| Input frequency: | 50 / 60 Hz (auto detection) |
| Output voltage: | 230 V AC \pm 10 % (Approximated Sine Wave) |
| Output frequency: | 50 / 60 Hz \pm 1 % |
| Transfer time: | 4 ms |
| Typical battery charge time: | 6 hours |
| Battery: | Maintenance-free, closed lead-acid battery |
| Estimated battery operation time: | <ul style="list-style-type: none"> • 30 minutes @ 60 W • 20 minutes @ 90 W |
| Number of outputs: | 3 pcs |
| Protections: | <ul style="list-style-type: none"> • Overvoltage • Overload protection • Overcharge protection • Protection: DSL / Tel / FAX / Modem - RJ11 / RJ45 |



DATA SHEET

| | |
|--------------------------------------|---|
| Operation state indication: | <ul style="list-style-type: none">• LED diodes,• Sound signaling |
| Main features: | <ul style="list-style-type: none">• Auto restart while AC is recovering• Automatic Voltage Regulator (AVR)• Compatible with power generators• Battery Management Technology - Increased battery life• Fireproof housing• Built-in EMI, RFI filter• Configurable alarm |
| Application: | <ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment |
| Housing type: | Tower |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 0 ... 90 % |
| Weight: | 4.26 kg |
| Dimensions: | 82 x 173 x 287 mm |
| Manufacturer / Brand: | CyberPower |
| Guarantee: | 2 years |