DATA SHEET

Code: HAC-HFW1500R-Z-IRE6-A-2712

AHD, HD-CVI, HD-TVI, PAL CAMERA **HAC-HFW1500R-Z-IRE6-A-2712** - 5 Mpx 2.7 ... 12 mm - MOTOZOOM DAHUA

Megapixel camera with 1/2.7" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.
The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.
Camera is according to IP67 Index of Protection norm.



Standard:	AHD / HD-CVI / HD-TVI / PAL
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	2592 x 1944 - 5 Mpx : Aspect Ratio 4 : 3 , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p , 960 x 576 - 960H, PAL
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Lens:	2.7 ... 12 mm - Motozoom
View angle:	• 98 ° ... 34 ° (manufacturer data) • 96 ° ... 30 ° (our tests result)
S/N ratio:	> 65 dB
Range of IR illumination:	60 m
IR illuminator power adjustment:	Automatic
Audio:	Microphone built-in - HD-CVI only

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Main features:	• Motozoom lens - The camera does not have auto-focus function • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Configurable Privacy Zones • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
OSD menu:	✔
Power supply:	12 V DC / 1 A
Power consumption:	≤ 12 W
Housing:	Compact, Aluminum
Color:	White
"Index of Protection":	IP67
Operation temp:	-40 °C ... 60 °C
Weight:	0.55 kg
Dimensions:	210 x 90 x 90 mm
Manufacturer / Brand:	DAHUA
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60