# DATA SHEET

Code: NVR5216-8P-4KS2E

## NVR **NVR5216-8P-4KS2E** 16 CHANNELS, 8 PoE DAHUA



| | |
|---|---|
| Standard: | TCP/IP |
| Supported resolutions: | max. 12 Mpx - 4000 x 3000 px |
| Video outputs: | 1 pcs HDMI 4K<br>1 pcs VGA |
| Audio support: | 16 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH - External microphone input |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265 / H.265+ / H.264 / H.264+ / MJPEG |
| USB: | 1 pcs USB 2.0<br>1 pcs USB 3.0 |
| Supported hard drives: | 2 x 10 TB SATA III |
| Recording modes: | Manual, Sensor, Motion detection, Schedule |
| Network protocols: | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, PPPoE, IP Filter, FTP, IP Search, Alarm Server, P2P, ONVIF 2.4 |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy) |
| Bitrate: | max. 320 Mbps |
| Network functions: | Full support via network, Remote records copying, Web Server built-in<br>max. 128 on-line users |
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application DMSS<br>• iOS (iPhone): Free application DMSS<br><br>See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Default IP address: | 192.168.1.108 |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

# DATA SHEET

| | |
|---|---|
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| RTSP URL: | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Alarm inputs / outputs: | 4 / 2 |
| PTZ control: | RS-485, PELCO-D/P IP Speed Dome Cameras |
| Motion Detection: | 22 x 18 motion zones - after motion detection records detected channels only |
| Intelligent Image Analysis: | ✔ |
| Mouse support: | ✔ |
| IR remote controller in the set: | – |
| Switch PoE: | • 8-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at), max. 130 W (total)<br>• ePoE : 1 ... 8 ports |
| Power supply: | 100 ... 240 V AC @ 50 / 60 Hz |
| Weight: | 2.65 kg |
| Dimensions: | 375 x 327 x 53 mm |
| Supported languages: | Polish, English, Bulgarian, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Slovenian, Serbian, Swedish, Hungarian, Italian |
| Country of origin: | China |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | **3 years** |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60