

DATA SHEET

Code: S5500-48GT4XF

INDUSTRIAL SWITCH **S5500-48GT4XF** 48-PORT SFP DAHUA

The S5500-48GT4XF switch is designed for large streams of video data in the CCTV IP surveillance networks. Designed to continuous operation 24/7.



| LAN ports: | 48 x RJ45 - 10/100/1000 Base-T |
|----------------------|---|
| Transmission speed: | • 10 / 100 / 1000 Mbps - 48 LAN ports, • 1000 Mbps - 4 SFP ports |
| Management: | → |
| MAC addresses table: | 16k |
| Main features: | Switch is managed via a web browser, command line interface and SNMP, RMON protocols OoS/DSCP priority based on IEEE 802.1p standard Queue scheduling: SP, WRR, SP+WRR Port/flow-based rate limiting IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support IEEE 802.1Q standard support, up to 512 VLAN groups and 4K VIDs IGMP Snooping V1/V2/V3 IRF2 - technology allowing virtual connection of several physical devices into one logical device and managing it as a single device; The system based on the IRF technology also allows to build a system of many parallel connected devices, which translates into increased system performance, greater resistance to failures, the ability to connect redundant devices in the 1:N system with the possibility of replacing any device at any time without affecting the operation of the entire system (Hot Swap), Support ARP Spoofing defence BPDU Filtering/Guard Data Flow Control (802.3x) protection against lightning discharges and voltage differences and strokes between devices |
| Certificates: | CE, RoHS |
| Power supply: | 230 V AC |
| Power consumption: | ≤ 45 W |
| Operation temp: | 0 °C 45 °C |
| Weight: | 3.69 kg |
| Dimensions: | 440 x 260 x 44 mm |





DATA SHEET

| Manufacturer / Brand: | DAHUA |
|-----------------------|---------|
| Guarantee: | 3 years |