

DATA SHEET

Code: ASP-215-R WIRELESS INDOOR SIREN ASP-215-R ABAX/ABAX2 SATEL



Indoor, wireless controlled optical-acoustical siren designed for operation in the intruder alarm systems. Optical signaling source are LEDs, and acoustical signaling is generating by piezo transducer.

High-impact polycarbonate enclosure, featuring a very high mechanical strength and guarantees aesthetic appearance of siren even after many years of using. Construction enables high level of tamper protection (against opening and removing from mounting surface). The ASP-215-R supports the other devices copmpatible with wireless ABAX/ABAX2

system.

| Support: | ABAX/ABAX2 |
|---|--|
| Frequency band: | 868 MHz 868.6 MHz |
| Radio communication range (at open area): | • ≤ 2000 m - ABAX2 @ ACU-220, • ≤ 1600 m - ABAX2 @ ACU-280, • ≤ 500 m - ABAX |
| Main features: | Tamper protection (detection of removing from mounting surface and enclosure opening) Remote configuration Optical and acoustic signaling is triggered independently, by radio Housing made of high impact polycarbonate, characterized by very high mechanical strength The "ECO" option allows to extend the battery life up to four times (only in ABAX2) |
| Protection class (Grade): | 2 |
| Power supply: | Lithium battery CR123A (included) |
| Current consumption: | max. 40 mA |
| Backup time: | ≤ 2 years |
| Operation temp: | -10 °C 55 °C |



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

| Weight: | 0.16 kg |
|-----------------------|------------------|
| Dimensions: | 87 x 133 x 37 mm |
| Manufacturer / Brand: | SATEL |
| Guarantee: | 2 years |

