

Code: DS-PWA32-HSR

WIRELESS ALARM CONTROL PANEL **DS-PWA32-HSR** Hikvision

The DS-PWA32-HSR wireless alarm control panel supports 32 wireless alarm inputs and 32 wireless outputs. In addition, the device allows to handle max. 2 wireless sirens and up to 8 remote controls.



Number of supported wireless detectors:	max. 32 pcs
Number of supported remote control keyfobs:	max. 8 pcs
The RFID cards/keyfobs support:	max. 12 pcs, In the kit : 5 pcs
Number of supported wireless sirens:	max. 2 pcs (not included)
Operating frequency range of the wireless devices:	868 MHz
Operating range in open area:	max. 800 m
Partitions:	1 pcs
Timers:	—
Users + admins:	11 + 2
Keyboard included:	—
Expander included :	—
Built-in modules:	• Wi-Fi module IEEE 802.11 b/g/n, 2.4 GHz • LAN, 10/100Mb • GPRS, 3/4G module - It supports push messages, SMS text notifications, and audio notifications via the phone
Access from PC:	iVMS-4200 application
Mobile phones support:	✓
Power supply:	5 V DC / 2 A (power adapter included)

Main features:	• Support for bidirectional communication of alarm events and other signals via the LAN, Wi-Fi, GPRS, 3G/4G networks using the main and backup channels • Support for video events via a mobile client and email • Configuration via the www client, mobile client or software • Compliance with the SIA-Contact ID protocol • Speaker built-in • Emergency Power Supply : built-in battery Li-Ion 3.8 V / 4520 mAh - 17.176 Wh
Housing:	Plastic
Color:	White
Operation temp:	-10 °C ... 55 °C
Dimensions:	155 x 155 x 35 mm
Manufacturer / Brand:	Hikvision
SAP Code:	302401105
Guarantee:	3 years