

Code: DS-KD8003-IME1/FLUSH/EU

## VIDEO DOORPHONE MODULE **DS-KD8003-IME1/FLUSH/EU** Hikvision

The DS-KD8003-IME1/FLUSH/EU is the main unit of the video doorphone modular system of the Hikvision brand. Using the DS-KD8003-IME1/FLUSH/EU main unit, the video doorphone system can be extended to a maximum of 8 extension modules. Video Doorphone is mounted in a flush-mounted housing.



Compatibility:	Hikvision - DS-KD-xx
Doorbell button:	1 pcs
Sensor:	2.1 Mpx CMOS
Camera resolution:	1920 x 1080 - 1080p
Camera view angle:	180 °
Image compression method:	H.264
IR illuminator:	✓
Ethernet:	10/100 Mb/s
Network protocols:	TCP/IP, RTSP
Alarm inputs:	4 pcs
Relay outputs:	2 x NO/NC



# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• Bidirectional communication,</li><li>• Microphone built-in,</li><li>• Speakers built-in,</li><li>• Noise suppression and echo cancellation,</li><li>• Tamper detection - removing from mounting surface,</li><li>• Video Doorphone is mounted in a flush-mounted housing</li></ul>
Power supply:	<ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC</li></ul>
Power consumption:	≤ 10 W
Operation temp:	-40 °C ... 60 °C
Housing:	Metal
Color:	Graphite
"Index of Protection":	IP65
Weight:	0.64 kg
Dimensions:	124 x 134 x 37 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305301496
Guarantee:	<b>3 years</b>