

Code: AT-UPS600-LED

UPS **AT-UPS600-LED** 600 VA EAST

The AT-UPS600-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.



Nominal power:	360 W
Apparent Power:	600 VA
Input voltage:	162 V ... 295 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	2 ... 7 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	1 pcs - 12V/7Ah
Estimated battery operation time:	10 ... 20 minutes - depending on the load
Number of outputs:	2 pcs CEE 7/3 (Schuko)



DATA SHEET

Protections:	<ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• Overcharge protection• Discharge
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling
Main features:	<ul style="list-style-type: none">• Automatic Voltage Regulator (AVR)• Configurable alarm• COLD START: - Cold start of the power adapter
Application:	<ul style="list-style-type: none">• Surveillance Systems• data storage centers• network, servers, workstations• Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	4.24 kg
Dimensions:	300 x 100 x 142 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years