

Code: SD22404T-GN-W

IP SPEED DOME CAMERA **SD22404T-GN-W** Wi-Fi, - 4 Mpx 2.7 ... 11 mm DAHUA

IP camera equipped with very good high resolution sensor. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m. For a few models of IP cameras working at 4Mpx resolution we recommend to use of network with 1Gb/s bandwidth.



| | |
|----------------------------------|---|
| Standard: | TCP/IP |
| Sensor: | 1/3 " Progressive Scan CMOS |
| Matrix size: | 4 Mpx |
| Resolution: | 2592 x 1520 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p |
| IR illuminator: | — |
| Lens: | 2.7 ... 11 mm |
| View angle: | <ul style="list-style-type: none"> • 113 ° ... 30 ° (manufacturer data) • 100 ° ... 33 ° (our tests result) |
| Optical zoom: | x 4 |
| Digital zoom: | x 16 |
| Min. illumination: | 0.05 Lux (color) 0.005 Lux (B/W) |
| S/N ratio: | > 50 dB (AGC off) |
| Preset rotation speed: | <ul style="list-style-type: none"> • 100 °/s (horizontal) • 60 °/s (vertical) |
| Rotation speed (manual control): | <ul style="list-style-type: none"> • 0.1 °/s ... 100 °/s (horizontal) • 0.1 °/s ... 60 °/s (vertical) |
| Horizontal rotation range: | 0 ... 355 ° - Rotation of the head is limited by stops |
| Vertical rotation range: | 0 ° ... 90 ° |



DATA SHEET

| | |
|-------------------------------|---|
| Protocols: | DH-SD |
| RS-485 interface: | — |
| Number of presets: | 300 |
| Horizontal scan: | ✓ |
| Route settings: | 5 |
| Image compression method: | H.265 / H.264 / MJPEG |
| Audio: | — |
| Bitrate: | 448 ... 8192 kbps |
| Alarm inputs / outputs: | — |
| Main stream frame rate: | 25 fps @ 4 Mpx |
| Network interface: | 10/100 Base-TX (RJ-45) |
| Network protocols: | IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, IEEE 802.1x |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| WEB Server: | Built-in, NVR compliance |
| Max. number of on-line users: | 20 |
| ONVIF: | 16.12 |
| Mobile phones support: | Port 37777 • Android: DMSS free application • iOS (iPhone): DMSS free application |
| Main features: | <ul style="list-style-type: none">• Wi-Fi Module - IEEE 802.11 a/b/g/n/ac, Range : 50 m (open area) ; Antenna - SMA socket• WDR - 120 dB - Wide Dynamic Range• 2D-DNR, 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• ROI - improve the quality of selected parts of image• BLC/HLC - Back Light / High Light Compensation• Configurable Privacy Zones• Motion Detection• Sharpness - sharper image outlines• ICR - Movable InfraRed filter• Mirror - Mirror image• AGC - Automatic Gain Control• Day/Night mode (color/b&w/auto)• IVS analysis : face detection, crossing the line (tripwire), intrusion, abandoned/missing object |
| Power supply: | 12 V DC / 830 mA |
| Power consumption: | ≤ 10 W |
| Housing: | Speed Dome, Metal |
| Color: | White |
| Supported languages: | Polish, English |
| Operation temp: | -30 °C ... 60 °C |
| "Index of Protection": | IP66 |



DATA SHEET

| | |
|-----------------------|----------------|
| Vandal-proof: | IK10 |
| Weight: | 0.62 kg |
| Dimensions: | Ø 123 x 89 mm |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |